

CBR500R

Honda BigBike

— EXCITES THE WORLD —



Full LED Lighting

The CBR500R features an all-LED lighting system for optimal energy efficiency. The sharp headlights design provide the CBR500R with a sporty yet contemporary design silhouette.



Cockpit Control

The CBR500R features a concise Liquid Crystal Display (LCD) odometer panel which display speed and rev counter, dual trip meters, fuel level and consumption gauges and a gear position indicator.



Twin-Cylinder Engine

The 8-valve, liquid-cooled parallel twin-cylinder engine produces 37kW @ 8,500rpm with a peak torque of 45Nm @ 6,500rpm. Revised camshaft and valve lift have increased low- and mid-range torque for faster acceleration.




Assist / Slipper Clutch

Shifting through the six-speed gearbox on the CBR500R has been made easy with assist / slipper clutch feature. It will assist the rider to attack a corner in the full confident without the fear of locking up the rear wheel.



Anti-Lock Brake System (ABS)

The new CBR500R features a single front 310mm wavy disc and powerful two-piston brake caliper matched to a 240mm rear disc and single piston caliper. Dual channel ABS is fitted as standard.



Emergency Stop Signal

The CBR500R's Emergency Stop Signal system detects sudden braking and automatically activates the front and rear hazard lights, which flash to warn any nearby vehicles.



*Colours and photos may vary from the actual product.

SPECIFICATIONS

ENGINE AND FUEL SYSTEM

Engine Type	Liquid-Cooled, 4 Stroke, DOHC
Displacement	471 cm ³
Bore x Stroke	67.0 mm x 66.8 mm
Compression Ratio	10.7 : 1
Max. Power	37 kW @ 8,500 rpm
Max. Torque	45 N.m @ 6,500 rpm
Engine Oil Capacity	3.2 l
Carburation	PGM-FI

TRANSMISSION

Clutch Type	Assist / Slipper Clutch, Wet Multiplate Type
Transmission Type	6 Speed, Mechanical (Chain drive)

DIMENSION AND WEIGHT

Dimensions (L x W x H)	2,080 mm x 755 mm x 1,145 mm
Wheelbase	1,410 mm
Caster Angle	25.5°
Trail	102 mm
Seat Height	785 mm
Ground Clearance	130 mm
Kerb Weight	192 kg
Fuel Tank Capacity	17.1 l

SUSPENSION

Suspension Type	Front: Telescopic, Pre-Load Adjustable Rear: Pro-link Mono with 5 Stage Preload Adjuster, Swingarm
-----------------	---

WHEELS AND BRAKE

Rim Size	Front: 17M/C X MT 3.50
	Rear: 17M/C X MT 4.50
Tyres	Front: 120/70ZR17M/C (58W) (Tubeless)
	Rear: 160/60ZR17M/C (69W) (Tubeless)
Brakes Type	Front: Hydraulic Disc, ABS
	Rear: Hydraulic Disc, ABS

COLOR VARIANT

	GRAND PRIX RED		MAT AXIS GRAY METALLIC
	PEARL METALLOID WHITE		

The destination for riders
Honda BigWing

Meet the various models of Honda BigBike
And the world-class experience that can be yours
at **Honda BigWing**, "The destination for riders."

All specifications are provisional and subject to change without notice.

- Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tyre pressure, installation of accessories, cargo, rider and passenger weight, and other factors.
- These models come with a 2 year or 20,000km manufacturing warranty (whichever comes first).

Toll Free Line
1800 883993

Monday – Friday (9am – 5pm)
Close on public holidays
<https://hondabigbike.com.my>

Honda Motorcycle Malaysia
 hondamotorcycle.my
 012-499 3991

AUTHORISED DEALER STAMP

size: 270x210mm